

Package ‘GenomicTuples’

October 27, 2015

Type Package

Title Representation and Manipulation of Genomic Tuples

Version 1.4.0

Date 2015-04-11

Author Peter Hickey <peter.hickey@gmail.com>, with contributions from Marcin Cieslik and Herve Pages.

Maintainer Peter Hickey <peter.hickey@gmail.com>

Description GenomicTuples defines general purpose containers for storing genomic tuples. It aims to provide functionality for tuples of genomic co-ordinates that are analogous to those available for genomic ranges in the GenomicRanges Bioconductor package.

URL www.github.com/PeteHaitch/GenomicTuples

BugReports <https://github.com/PeteHaitch/GenomicTuples/issues>

biocViews Infrastructure, DataRepresentation, Sequencing

VignetteBuilder knitr

Depends R (>= 3.2.0), GenomicRanges (>= 1.19.47), GenomeInfoDb, BiocGenerics, methods

Imports Rcpp (>= 0.11.2), S4Vectors, Biobase, IRanges

Suggests testthat, knitr, BiocStyle, rmarkdown

LinkingTo Rcpp

License Artistic-2.0

Collate 'AllGenerics.R' 'AllUtilities.R' 'GTuples-class.R'
'GTuples-comparison.R' 'GTuplesList-class.R' 'GenomicTuples.R'
'RcppExports.R' 'coverage-methods.R' 'findOverlaps-methods.R'
'inter-tuple-methods.R' 'intra-tuple-methods.R'
'mapCoords-methods.R' 'nearest-methods.R' 'setops-methods.R'
'tile-methods.R' 'zzz.R'

NeedsCompilation yes

R topics documented:

GenomicTuples-package	2
findOverlaps-methods	2
GTuples-class	5

GTuples-comparison	11
GTuplesList-class	14
intra-tuple-methods	18
nearest-methods	20
Undefined methods	23

Index 24

GenomicTuples-package *Representation and manipulation of genomic tuples.*

Description

GenomicTuples defines general purpose containers for storing genomic tuples. It aims to provide functionality for tuples of genomic co-ordinates that are analogous to those available for genomic ranges in the GenomicRanges Bioconductor package.

Details

Please refer to the vignettes to see how to use the **GenomicTuples** package.

findOverlaps-methods *Finding overlapping genomic tuples*

Description

Finds tuple overlaps between a [GTuples](#) or [GTuplesList](#) object, and another object containing tuples or ranges.

NOTE: The [findOverlaps](#) generic function and methods for [Ranges](#) and [RangesList](#) objects are defined and documented in the **IRanges** package. The methods for [GenomicRanges](#), [GRangesList](#), and [GIntervalTree](#) objects are defined and documented in the **GenomicRanges** package. The methods for [GAlignments](#), [GAlignmentPairs](#), and [GAlignmentsList](#) objects are defined and documented in the **GenomicAlignments** package.

Usage

```
## S4 method for signature 'GTuples,GTuples'
findOverlaps(query, subject,
             maxgap = 0L, minoverlap = 1L,
             type = c("any", "start", "end", "within", "equal"),
             select = c("all", "first", "last", "arbitrary"),
             algorithm = c("nclist", "intervaltree"),
             ignore.strand = FALSE)

## S4 method for signature 'GTuples,GTuples'
countOverlaps(query, subject,
              maxgap = 0L, minoverlap = 1L,
              type = c("any", "start", "end", "within", "equal"),
              algorithm = c("nclist", "intervaltree"),
              ignore.strand = FALSE)
```

```
## S4 method for signature 'GTuples,GTuples'
overlapsAny(query, subject,
  maxgap = 0L, minoverlap = 1L,
  type = c("any", "start", "end", "within", "equal"),
  algorithm = c("nclist", "intervaltree"),
  ignore.strand = FALSE)

## S4 method for signature 'GTuples,GTuples'
subsetByOverlaps(query, subject,
  maxgap = 0L, minoverlap = 1L,
  type = c("any", "start", "end", "within", "equal"),
  algorithm = c("nclist", "intervaltree"),
  ignore.strand = FALSE)
```

Arguments

`query`, `subject` A [GTuples](#) or [GTuplesList](#) object. [GRanges](#), [GRangesList](#), [RangesList](#) and [RangedData](#) are also accepted for one of `query` or `subject`.

`type` See details below.

`algorithm` Please see `GenomicRanges::findOverlaps`.

`maxgap`, `minoverlap` See [findOverlaps](#) in the `IRanges` package for a description of these arguments. These arguments have no effect if both `query` and `subject` are [GTuples](#) objects and `type = "equal"`.

`select` See [findOverlaps](#) in the `IRanges` package for a description of this argument.

`ignore.strand` When set to `TRUE`, the strand information is ignored in the overlap calculations.

Details

The `findOverlaps`-based methods involving genomic tuples, either through [GTuples](#) or [GTuplesList](#) objects, can search for *tuple-tuple*, *tuple-range* and *range-tuple* overlaps. Each of these are described below, with attention paid to the important special case of finding "equal tuple-tuple overlaps".

Equal tuple-tuple overlaps When the `query` and the `subject` are both [GTuples](#) objects and `type = "equal"`, `findOverlaps` uses the `seqnames` ([seqnames](#)), positions ([tuples](#), [GTuples-method](#)) and strand ([strand](#)) to determine which tuples from the `query` exactly match those in the `subject`, where a strand value of "*" is treated as occurring on both the "+" and "-" strand. An overlap is recorded when a tuple in the `query` and a tuple in the `subject` have the same sequence name, have a compatible pairing of strands (e.g. `"+"/"+"`, `"-"/"-"`, `"*"/"+"`, `"*"/"-"`, etc.), and have identical positions.

NOTE: Equal tuple-tuple overlaps can only be computed if `size(query)` is equal to `size(subject)`.

Other tuple-tuple overlaps When the `query` and the `subject` are [GTuples](#) or [GTuplesList](#) objects and `type = "any"`, `"start"`, `"end"` or `"within"`, `findOverlaps` treats the tuples as if they were ranges, with ranges given by $[pos_1, pos_m]$ and where m is the `size`, [GTuples-method](#) of the tuples. This is done via inheritance so that a [GTuples](#) (resp. [GTuplesList](#)) object is treated as a [GRanges](#) (resp. [GRangesList](#)) and the appropriate `findOverlaps` method is dispatched upon.

NOTE: This is the only type of overlap finding available when either the `query` and `subject` are [GTuplesList](#) objects. This is following the behaviour of [findOverlaps](#), [GRangesList](#), [GRangesList-method](#) that allows `type = "any"`, `"start"`, `"end"` or `"within"` but does not allow `type = "equal"`.

tuple-range and range-tuple overlaps When one of the query and the subject is not a [GTuples](#) or [GTuplesList](#) objects, `findOverlaps` treats the tuples as if they were ranges, with ranges given by $[pos_1, pos_m]$ and where m is the [size, GTuples-method](#) of the tuples. This is done via inheritance so that a [GTuples](#) (resp. [GTuplesList](#)) object is treated as a [GRanges](#) (resp. [GRangesList](#)) and the appropriate `findOverlaps` method is dispatched upon.

In the context of `findOverlaps`, a feature is a collection of tuples/ranges that are treated as a single entity. For [GTuples](#) objects, a feature is a single tuple; while for [GTuplesList](#) objects, a feature is a list element containing a set of tuples. In the results, the features are referred to by number, which run from 1 to `length(query)/length(subject)`.

When the query is a [GTuples](#) or [GTuplesList](#) object then the subject can be a [GIntervalTree](#) object. For repeated queries against the same subject, it is more efficient to create a [GIntervalTree](#) once for the subject using the [GIntervalTree](#) constructor described below and then perform the queries against the [GIntervalTree](#) instance. **NOTE:** [GIntervalTree](#) objects only support genomic ranges and not genomic tuples, and are not supported for circular genomes.

Value

For `findOverlaps` either a [Hits](#) object when `select = "all"` or an integer vector otherwise.

For `countOverlaps` an integer vector containing the tabulated query overlap hits.

For `overlapsAny` a logical vector of length equal to the number of tuples/ranges in query indicating those that overlap any of the tuples/ranges in subject.

For `subsetByOverlaps` an object of the same class as query containing the subset that overlapped at least one entity in subject.

For `RangedData` and `RangesList`, with the exception of `subsetByOverlaps`, the results align to the unlisted form of the object. This turns out to be fairly convenient for `RangedData` (not so much for `RangesList`, but something has to give).

Author(s)

Peter Hickey for methods involving [GTuples](#) and [GTuplesList](#). P. Aboyoun, S. Falcon, M. Lawrence, N. Gopalakrishnan, H. Pages and H. Corrada Bravo for all the real work underlying the powerful `findOverlaps` functionality.

See Also

- Please see the package vignette for an extended discussion of overlaps involving genomic tuples, which is available by typing `vignette(topic = 'GenomicTuplesIntroduction', package = 'GenomicTuples')` at the R prompt.
- [findOverlaps](#)
- [findOverlaps](#)
- [Hits-class](#)
- [GTuples-class](#)
- [GTuplesList-class](#)
- [GRanges-class](#)
- [GRangesList-class](#)
- [GIntervalTree-class](#)

Examples

```

## GTuples object containing 3-tuples:
gt3 <- GTuples(seqnames = c('chr1', 'chr1', 'chr1', 'chr1', 'chr2'),
              tuples = matrix(c(10L, 10L, 10L, 10L, 10L, 20L, 20L, 20L, 25L,
                              20L, 30L, 30L, 35L, 30L, 30L), ncol = 3),
              strand = c('+', '-', '*', '+', '+'))

## GTuplesList object
gtl3 <- GTuplesList(A = gt3[1:3], B = gt3[4:5])

## Find equal genomic tuples:
findOverlaps(gt3, gt3, type = 'equal')
## Note that this is different to the results if the tuples are treated as
## ranges since this ignores the "internal positions" (pos2):
findOverlaps(granges(gt3), granges(gt3), type = 'equal')

## Scenarios where tuples are treated as ranges:
findOverlaps(gt3, gt3, type = 'any')
findOverlaps(gt3, gt3, type = 'start')
findOverlaps(gt3, gt3, type = 'end')
findOverlaps(gt3, gt3, type = 'within')

## Overlapping a GTuples and a GTuplesList object (tuples treated as ranges):
table(!is.na(findOverlaps(gtl3, gt3, select="first")))
countOverlaps(gtl3, gt3)
findOverlaps(gtl3, gt3)
subsetByOverlaps(gtl3, gt3)
countOverlaps(gtl3, gt3, type = "start")
findOverlaps(gtl3, gt3, type = "start")
subsetByOverlaps(gtl3, gt3, type = "start")
findOverlaps(gtl3, gt3, select = "first")

```

GTuples-class

*GTuples objects***Description**

The `GTuples` class is a container for the genomic tuples and their associated annotations.

Details

`GTuples` extends `GRanges` as a container for genomic tuples rather than genomic ranges. `GTuples` is a vector of genomic locations and associated annotations. Each element in the vector is comprised of a sequence name, a tuple, a `strand`, and optional metadata columns (e.g. score, GC content, etc.). This information is stored in four components:

`seqnames` a 'factor' `Rle` object containing the sequence names.

`tuples` externally, a matrix-link object containing the tuples. Internally, an `IRanges` object storing the first and last position of each tuple and, if required, a matrix storing the "internal" positions of each tuple (see description of `internalPos` below).

`strand` a `Rle` `Rle` object containing the strand information.

`mcols` a `DataFrame` object containing the metadata columns. Columns cannot be named "seqnames", "ranges", "tuples", "internalPos", "size", "strand", "seqlevels", "seqlengths", "isCircular", "start", "end", "width", or "element".

`seqinfo` a `DataFrame` object containing information about the set of genomic sequences present in the `GTuples` object.

Slots

Since the `GTuples` class extends the `GRanges` class it contains the `seqnames`, `ranges`, `strand`, `elementMetadata`, `seqinfo` and `metadata`. The `GTuples` class also contains two additional slots, `size` and `internalPos`.

`size` An integer. The size of the genomic tuples stored in the `GTuples` object.

`internalPos` If the size of the genomic tuples is greater than 2, `internalPos` is an integer matrix storing the "internal" positions of each genomic tuple. Otherwise `internalPos` is `NULL`.

Constructor

`GTuples(seqnames = Rle(), tuples = matrix(), strand = Rle("*", length(seqnames)), ..., seqlengths = integer(), seqinfo = DataFrame(), metadata = DataFrame())`
Creates a `GTuples` object.

`seqnames` `Rle` object, character vector, or factor containing the sequence names.

`tuples` matrix object containing the positions of the tuples. The first column should refer to `pos1`, the second to `pos2`, etc.

`strand` `Rle` object, character vector, or factor containing the strand information.

`...` Optional metadata columns. These columns cannot be named "start", "end", "width", or "element". A named integer vector "seqlength" can be used instead of `seqinfo`.

`seqlengths` an integer vector named with the sequence names and containing the lengths (or `NA`) for each `level(seqnames)`.

`seqinfo` a `DataFrame` object containing allowed sequence names and lengths (or `NA`) for each `level(seqnames)`.

Coercion

In the code snippets below, `x` is a `GTuples` object.

`as.data.frame(x, row.names = NULL, optional = FALSE, ...)`: Creates a `data.frame` with columns `seqnames` (factor), `tuples` (integer), `strand` (factor), as well as the additional metadata columns stored in `mcols(x)`. Pass an explicit `stringsAsFactors=TRUE/FALSE` argument via `...` to override the default conversions for the metadata columns in `mcols(x)`.

`as(x, "GRanges"), granges(x)`: Creates a `GRanges` object from a `GTuples` object. **WARNING:** This is generally a *destructive* operation, as the original `GTuples` may not be re-creatable.

Accessors

In the following code snippets, `x` is a `GTuples` object.

`size(x)`: Get the size of the genomic tuples stored in `x`.

`length(x)`: Get the number of elements.

`seqnames(x), seqnames(x) <- value`: Get or set the sequence names. `value` can be an `Rle` object, a character vector, or a factor.

`tuples(x)`, `tuples(x) <- value`: Get the positions of the tuples, which are returned as an integer matrix. `value` can be an integer matrix.

`ranges(x, use.mcols = FALSE)`, `ranges(x) <- value`: Get or set the ranges in the form of a `CompressedIRangesList`. `value` can be a `RangesList` object.

WARNING: The use of `ranges` with `GTuples` objects is **strongly** discouraged. It will only get/set pos_1 and pos_m of the tuples, where m is the size of the tuples, as these are what are stored in the "ranges" slot of a `GTuples` object.

`names(x)`, `names(x) <- value`: Get or set the names of the elements.

`strand(x)`, `strand(x) <- value`: Get or set the strand. `value` can be an `Rle` object, character vector, or factor.

`mcols(x, use.names=FALSE)`, `mcols(x) <- value`: Get or set the metadata columns. If `use.names=TRUE` and the metadata columns are not `NULL`, then the names of `x` are propagated as the row names of the returned `DataFrame` object. When setting the metadata columns, the supplied value must be `NULL` or a data.frame-like object (i.e. `DataTable` or `data.frame`) object holding element-wise metadata.

`elementMetadata(x)`, `elementMetadata(x) <- value`, `values(x)`, `values(x) <- value`: Alternatives to `mcols` functions. Their use is discouraged.

`seqinfo(x)`, `seqinfo(x) <- value`: Get or set the information about the underlying sequences. `value` must be a `DataFrame` object.

`seqlevels(x)`, `seqlevels(x, force=FALSE) <- value`: Get or set the sequence levels. `seqlevels(x)` is equivalent to `seqlevels(seqinfo(x))` or to `levels(seqnames(x))`, those 2 expressions being guaranteed to return identical character vectors on a `GTuples` object. `value` must be a character vector with no `NA`s. See `?seqlevels` for more information.

`seqlengths(x)`, `seqlengths(x) <- value`: Get or set the sequence lengths. `seqlengths(x)` is equivalent to `seqlengths(seqinfo(x))`. `value` can be a named non-negative integer or numeric vector eventually with `NA`s.

`isCircular(x)`, `isCircular(x) <- value`: Get or set the circularity flags. `isCircular(x)` is equivalent to `isCircular(seqinfo(x))`. `value` must be a named logical vector eventually with `NA`s.

`genome(x)`, `genome(x) <- value`: Get or set the genome identifier or assembly name for each sequence. `genome(x)` is equivalent to `genome(seqinfo(x))`. `value` must be a named character vector eventually with `NA`s.

`seqlevelsStyle(x)`, `seqlevelsStyle(x) <- value`: Get or set the seqname style for `x`. See the `seqlevelsStyle` generic getter and setter in the **GenomeInfoDb** package for more information.

`score(x)`, `score(x) <- value`: Get or set the "score" column from the element metadata.

Tuples methods

In the following code snippets, `x` is a `GTuples` object. **WARNING:** The preferred setter is `tuples(x) <- value` and the use of `start(x) <- value`, `end(x) <- value` and `width(x) <- value` is discouraged.

`start(x)`, `start(x) <- value`: Get or set pos_1 of the tuples. **WARNING:** The use of `width(x) <- value` is discouraged; instead, construct the tuples as the appropriate integer matrix, `mvalue`, and use `tuples(x) <- mvalue`.

`end(x)`, `end(x) <- value`: Get or set pos_m of the tuples, where m is the size of the tuples. **WARNING:** The use of `end(x) <- value` is discouraged; instead, construct the tuples as the appropriate integer matrix, `mvalue`, and use `tuples(x) <- mvalue`.

`IPD(x)`: Get the intra-pair distances (IPD). IPD is only defined for tuples with size > 1. The IPD of a tuple with size = m is the vector of intra-pair distances, $(pos_2 - pos_1, \dots, pos_m - pos_{m-1})$.

`width(x), width(x) <- value`: Get or set $pos_m - pos_1$ of the tuples, where m is the size of the tuples. If using `width(x) <- value`, pos_1 is held fixed and pos_m is altered. **WARNING**: The use of `width(x) <- value` is discouraged; instead, construct the tuples as the appropriate integer matrix, `mvalue`, and use `tuples(x) <- mvalue`.

Splitting and Combining

In the following code snippets, `x` is a `GTuples` object.

`append(x, values, after = length(x))`: Inserts the values into `x` at the position given by `after`, where `x` and `values` are of the same class.

`c(x, ...)`: Combines `x` and the `GTuples` objects in `...` together. Any object in `...` must belong to the same class as `x`, or to one of its subclasses, or must be `NULL`. The result is an object of the same class as `x`.

`c(x, ..., ignore.mcols=FALSE)` If the `GTuples` objects have metadata columns (represented as one `DataFrame` per object), each such `DataFrame` must have the same columns in order to combine successfully. In order to circumvent this restraint, you can pass in an `ignore.mcols=TRUE` argument which will combine all the objects into one and drop all of their metadata columns.

`split(x, f, drop=FALSE)`: Splits `x` according to `f` to create a `GTuplesList` object. If `f` is a list-like object then `drop` is ignored and `f` is treated as if it was `rep(seq_len(length(f)), sapply(f, length))`, so the returned object has the same shape as `f` (it also receives the names of `f`). Otherwise, if `f` is not a list-like object, empty list elements are removed from the returned object if `drop` is `TRUE`.

Subsetting

In the following code snippets, `x` is a `GTuples` object.

`x[i, j], x[i, j] <- value`: Get or set elements `i` with optional metadata columns `mcols(x)[, j]`, where `i` can be missing; an NA-free logical, numeric, or character vector; or a 'logical' `Rle` object.

`x[i, j] <- value`: Replaces elements `i` and optional metadata columns `j` with `value`.

`head(x, n = 6L)`: If `n` is non-negative, returns the first `n` elements of the `GTuples` object. If `n` is negative, returns all but the last `abs(n)` elements of the `GTuples` object.

`rep(x, times, length.out, each)`: Repeats the values in `x` through one of the following conventions:

`times` Vector giving the number of times to repeat each element if of length `length(x)`, or to repeat the whole vector if of length 1.

`length.out` Non-negative integer. The desired length of the output vector.

`each` Non-negative integer. Each element of `x` is repeated `each` times.

`subset(x, subset)`: Returns a new object of the same class as `x` made of the subset using logical vector `subset`, where missing values are taken as `FALSE`.

`tail(x, n = 6L)`: If `n` is non-negative, returns the last `n` elements of the `GTuples` object. If `n` is negative, returns all but the first `abs(n)` elements of the `GTuples` object.

`window(x, start = NA, end = NA, width = NA, frequency = NULL, delta = NULL, ...)`: Extracts the subsequence window from the `GTuples` object using:

`start, end, width` The start, end, or width of the window. Two of the three are required.

frequency, delta Optional arguments that specify the sampling frequency and increment within the window.

In general, this is more efficient than using "[" operator.

`window(x, start = NA, end = NA, width = NA, keepLength = TRUE) <- value`: Replaces the subsequence window specified on the left (i.e. the subsequence in `x` specified by `start`, `end` and `width`) by `value`. `value` must either be of class `class(x)`, belong to a subclass of `class(x)`, be coercible to `class(x)`, or be `NULL`. If `keepLength` is `TRUE`, the elements of `value` are repeated to create a `GTuples` object with the same number of elements as the width of the subsequence window it is replacing. If `keepLength` is `FALSE`, this replacement method can modify the length of `x`, depending on how the length of the left subsequence window compares to the length of `value`.

`x$name, x$name <- value`: Shortcuts for `mcols(x)$name` and `mcols(x)$name <- value`, respectively. Provided as a convenience, from `GRanges` as the result of strong popular demand. Note that those methods are not consistent with the other `$` and `$<-` methods in the `IRanges/ GenomicRanges` infrastructure, and might confuse some users by making them believe that a `GRanges` object can be manipulated as a `data.frame`-like object. Therefore we recommend using them only interactively, and we discourage their use in scripts or packages. For the latter, use `mcols(x)$name` and `mcols(x)$name <- value`, instead of `x$name` and `x$name <- value`, respectively.

Other methods

item `show(x)`: By default the `show` method displays 5 head and 5 tail elements. This can be changed by setting the global options `showHeadLines` and `showTailLines`. If the object length is less than (or equal to) the sum of these 2 options plus 1, then the full object is displayed. Note that these options also affect the display of `GRanges`, `GAlignments` and `GAlignmentPairs` objects (defined in the `GenomicAlignments` package), as well as other objects defined in the `IRanges` and `Biostrings` packages (e.g. `IRanges` and `DNASTringSet` objects).

Author(s)

Peter Hickey

See Also

[GTuplesList-class](#), [seqinfo](#), [Vector-class](#), [Rle-class](#), [Ranges-class](#), [DataFrame](#), [GRanges-class](#), [intra-tuple-methods](#), [findOverlaps-methods](#), [nearest-methods](#),

Examples

```
## Create example 4-tuples
seqinfo <- Seqinfo(paste0("chr", 1:3), c(1000, 2000, 1500), NA, "mock1")
gt4 <- GTuples(seqnames = Rle(c("chr1", "chr2", "chr1", "chr3"),
                             c(1, 3, 2, 4)),
              tuples = matrix(c(1:10, 2:11, 3:12, 4:13), ncol = 4),
              strand = Rle(strand(c("-", "+", "x", "+", "-")),
                           c(1, 2, 2, 3, 2)),
              score = 1:10, GC = seq(1, 0, length = 10), seqinfo = seqinfo)

gt4

## Summarizing elements
table(seqnames(gt4))
sum(width(gt4))
```

```

summary(mcols(gt4)[,"score"])

## Renaming the underlying sequences
seqlevels(gt4)
seqlevels(gt4) <- sub("chr", "Chrom", seqlevels(gt4))
gt4
seqlevels(gt4) <- sub("Chrom", "chr", seqlevels(gt4)) # revert

## Combining objects
gt4_a <- GTuples(seqnames = Rle(c("chr1", "chr2", "chr1", "chr3"),
                               c(1, 3, 2, 4)),
                tuples = matrix(c(1:10, 21:30, 31:40, 41:50), ncol = 4),
                strand = Rle(strand(c("-", "+", "x", "+", "-")),
                             c(1, 2, 2, 3, 2)),
                score = 1:10, seqinfo = seqinfo)

gt4_b <- GTuples(seqnames = Rle(c("chr1", "chr2", "chr1", "chr3"),
                               c(1, 3, 2, 4)),
                tuples = matrix(c(101:110, 121:130, 131:140, 141:150),
                               ncol = 4),
                strand = Rle(strand(c("-", "+", "x", "+", "-")),
                             c(1, 2, 2, 3, 2)),
                score = 1:10, seqinfo = seqinfo)

some_gt4 <- c(gt4_a, gt4_b)

## all_gt4 <- c(gt4, gt4_a, gt4_b) ## (This would fail)
all_gt4 <- c(gt4, gt4_a, gt4_b, ignore.mcols=TRUE)

## The number of lines displayed in the 'show' method
## are controlled with two global options.
options("showHeadLines" = 7)
options("showTailLines" = 2)
all_gt4

## Revert to default values
options("showHeadLines"=NULL)
options("showTailLines"=NULL)

## Get the size of the tuples stored in the GTuples object
size(gt4)

## Get the tuples
tuples(gt4)

## Get the matrix of intra-pair distances (IPD)
IPD(all_gt4)

## Can't combine genomic tuples of different sizes
gt1 <- GTuples('chr1', matrix(30:40))
gt1
## Not run:
## Returns error
c(gt4, gt1)

## End(Not run)

```

 GTuples-comparison *Comparing and ordering genomic tuples*

Description

Methods for comparing and ordering the elements in one or more [GTuples](#) objects.

Usage

```
## duplicated()
## -----

## S4 method for signature 'GTuples'
duplicated(x, incomparables = FALSE, fromLast = FALSE,
           method = c("hash", "base"))

## match()
## -----

## S4 method for signature 'GTuples,GTuples'
match(x, table, nomatch = NA_integer_,
      incomparables = NULL, ignore.strand = FALSE)

## order() and related methods
## -----

## S4 method for signature 'GTuples'
order(..., na.last = TRUE, decreasing = FALSE)

## S4 method for signature 'GTuples'
sort(x, decreasing = FALSE, ignore.strand = FALSE, by)

## S4 method for signature 'GTuples'
rank(x, na.last = TRUE,
     ties.method = c("average", "first", "random", "max", "min"))

## Generalized element-wise (aka "parallel") comparison of 2 GTuples
## objects
## -----

## S4 method for signature 'GTuples,GTuples'
compare(x, y)
```

Arguments

`x`, `table`, `y` [GTuples](#) objects.
`incomparables` Not supported.

method	There are two methods implemented: hash (default) and base. The base method is not recommended as it is much slower when the GTuples object contains a large number of tuples.
fromLast, nomatch	See <code>?`GenomicRanges-comparison`</code> in the IRanges package for a description of these arguments.
ignore.strand	Whether or not the strand should be ignored when comparing 2 genomic tuples.
...	Additional GTuples objects used for breaking ties.
na.last	Ignored.
decreasing	TRUE or FALSE.
ties.method	A character string specifying how ties are treated. Only "first" is supported for now.
by	An optional formula that is resolved against <code>as.env(x)</code> ; the resulting variables are passed to <code>order</code> to generate the ordering permutation.

Details

Two elements of a GTuples object (i.e. two genomic tuples) are considered equal iff they are on the same underlying sequence and strand, and have the same positions (`tuples`). `duplicated()` and `unique()` on a GTuples object are conforming to this.

The "natural order" for the elements of a GTuples object is to order them (a) first by sequence level, (b) then by strand, (c) then by pos_1, \dots, pos_m . This way, the space of genomic tuples is totally ordered.

`order()`, `sort()`, and `rank()` on a GTuples object are using this "natural order".

Also `==`, `!=`, `<=`, `>=`, `<` and `>` on GTuples objects are using this "natural order".

`compare(x, y)`: Performs "generalized range-wise comparison" of x and y, that is, returns an integer vector where the i-th element is a code describing how the i-th element in x is qualitatively positioned relative to the i-th element in y.

A code that is < 0 , $= 0$, or > 0 , corresponds to $x[i] < y[i]$, $x[i] == y[i]$, or $x[i] > y[i]$, respectively.

WARNING: These predefined codes are not as detailed as those for `Ranges-comparison`. Specifically, only the sign of the code matters, not the actual value.

`match(x, table, nomatch = NA_integer_)`: Returns an integer vector of the length of x, containing the index of the first matching range in table (or `nomatch` if there is no matching range) for each tuple in x.

`duplicated(x, fromLast = FALSE, method = c("hash", "base"))`: Determines which elements of x are equal to elements with smaller subscripts, and returns a logical vector indicating which elements are duplicates. See `duplicated` in the `base` package for more details.

`unique(x, fromLast = FALSE, method = c("hash", "base"))`: Removes duplicate tuples from x. See `unique` in the `base` package for more details.

`x %in% table`: A shortcut for finding the ranges in x that match any of the tuples in table. Returns a logical vector of length equal to the number of tuples in x.

`findMatches(x, table)`: An enhanced version of `match` that returns all the matches in a `Hits` object.

`countMatches(x, table)`: Returns an integer vector of the length of x containing the number of matches in table for each element in x.

`order(...)`: Returns a permutation which rearranges its first argument (a `GTuples` object) into ascending order, breaking ties by further arguments. See `order` in the **BiocGenerics** package for more information.

`sort(x)`: Sorts `x`. See `sort` in the **base** package for more details.

`rank(x, na.last = TRUE, ties.method = c("average", "first", "random", "max", "min"))`
Returns the sample ranks of the tuples in `x`. See `rank` in the **base** package for more details.

Value

For `compare`: see Details section above.

For `selfmatch`: an integer vector of the same length as `x`.

For `duplicated`, `unique`, and `%in%`: see `?BiocGenerics::duplicated`, `?BiocGenerics::unique`, and `?%in%`.

For `findMatches`: a `Hits` object by default (i.e. if `select="all"`).

For `countMatches`: an integer vector of the length of `x` containing the number of matches in `table` for each element in `x`.

For `sort`: see `?BiocGenerics::sort`.

Author(s)

Peter Hickey

See Also

- The `GTuples` class.
- `GenomicRanges-comparison` in the **GRanges** package for comparing and ordering genomic ranges.
- `intra-tuple-methods` for intra-tuple transformations.
- `findOverlaps-methods` for finding overlapping genomic ranges.

Examples

```
## GTuples object containing 3-tuples:
gt3 <- GTuples(seqnames = c('chr1', 'chr1', 'chr1', 'chr1', 'chr2'),
               tuples = matrix(c(10L, 10L, 10L, 10L, 10L, 20L, 20L, 20L, 25L,
                                20L, 30L, 30L, 35L, 30L, 30L), ncol = 3),
               strand = c('+', '-', '*', '+', '+'))
gt3 <- c(gt3, rev(gt3[3:5]))

## -----
## A. ELEMENT-WISE (AKA "PARALLEL") COMPARISON OF 2 GTuples OBJECTS
## -----
gt3[2] == gt3[2] # TRUE
gt3[2] == gt3[5] # FALSE
gt3 == gt3[4]
gt3 >= gt3[3]

## -----
## B. duplicated(), unique()
## -----
duplicated(gt3)
unique(gt3)
```

```

## -----
## C. match(), %in%
## -----
table <- gt3[2:5]
match(gt3, table)
match(gt3, table, ignore.strand = TRUE)

## -----
## D. findMatches(), countMatches()
## -----
findMatches(gt3, table)
countMatches(gt3, table)

findMatches(gt3, table, ignore.strand = TRUE)
countMatches(gt3, table, ignore.strand = TRUE)

gt3_levels <- unique(gt3)
countMatches(gt3_levels, gt3)

## -----
## E. order() AND RELATED METHODS
## -----
order(gt3)
sort(gt3)
sort(gt3, ignore.strand = TRUE)

## TODO (TODO copied from GenomicRanges): Broken. Please fix!
#sort(gt3, by = ~ seqnames + start + end) # equivalent to (but slower than) above

score(gt3) <- rev(seq_len(length(gt3)))

## TODO (TODO copied from GenomicRanges): Broken. Please fix!
#sort(gt3, by = ~ score)

rank(gt3)

## -----
## F. GENERALIZED ELEMENT-WISE COMPARISON OF 2 GTuples OBJECTS
## -----
compare(gt3[3], gt3)

```

GTuplesList-class

GTuplesList objects

Description

The `GTuplesList` class is a container for storing a collection of `GTuples` objects. It is derived from `GRangesList`.

Constructor

`GTuplesList(...)`: Creates a `GTuplesList` object using `GTuples` objects supplied in ...

Accessors

In the following code snippets, `x` is a `GTuplesList` object.

`length(x)`: Get the number of list elements.

`names(x)`, `names(x) <- value`: Get or set the names on `x`.

`elementLengths(x)`: Get the length of each of the list elements.

`isEmpty(x)`: Returns a logical indicating either if the `GTuplesList` has no elements or if all its elements are empty.

`seqnames(x)`, `seqnames(x) <- value`: Get or set the sequence names in the form of an `RleList`. `value` can be an `RleList` or `CharacterList` object.

`tuples(x)`, `tuples(x) <- value`: Get or set the tuples in the form of a `SimpleList` of integer matrices. `value` can be a single integer matrix.

`ranges(x, use.mcols = FALSE)`, `ranges(x) <- value`: Get or set the ranges in the form of a `CompressedIRangesList`. `value` can be a `RangesList` object.

WARNING: The use of `ranges` with `GTuplesList` objects is **strongly** discouraged. It will only get/set `pos1` and `posm` of the tuples, where `m` is the size of the tuples, as these are what are stored in the "ranges" slot of the `GTuples` objects.

`strand(x)`, `strand(x) <- value`: Get or set the strand in the form of an `RleList`. `value` can be an `RleList`, `CharacterList` or single character. `value` as a single character converts all ranges in `x` to the same value; for selective strand conversion (i.e., mixed "+" and "-") use `RleList` or `CharacterList`.

`mcols(x, use.names=FALSE)`, `mcols(x) <- value`: Get or set the metadata columns. `value` can be `NULL`, or a data.frame-like object (i.e. `DataFrame` or `data.frame`) holding element-wise metadata.

`elementMetadata(x)`, `elementMetadata(x) <- value`, `values(x)`, `values(x) <- value`: Alternatives to `mcols` functions. Their use is discouraged.

`seqinfo(x)`, `seqinfo(x) <- value`: Get or set the information about the underlying sequences. `value` must be a `Seqinfo` object.

`seqlevels(x)`, `seqlevels(x, force=FALSE) <- value`: Get or set the sequence levels. `seqlevels(x)` is equivalent to `seqlevels(seqinfo(x))` or to `levels(seqnames(x))`, those 2 expressions being guaranteed to return identical character vectors on a `GTuplesList` object. `value` must be a character vector with no NAs. See `?seqlevels` for more information.

`seqlengths(x)`, `seqlengths(x) <- value`: Get or set the sequence lengths. `seqlengths(x)` is equivalent to `seqlengths(seqinfo(x))`. `value` can be a named non-negative integer or numeric vector eventually with NAs.

`isCircular(x)`, `isCircular(x) <- value`: Get or set the circularity flags. `isCircular(x)` is equivalent to `isCircular(seqinfo(x))`. `value` must be a named logical vector eventually with NAs.

`genome(x)`, `genome(x) <- value`: Get or set the genome identifier or assembly name for each sequence. `genome(x)` is equivalent to `genome(seqinfo(x))`. `value` must be a named character vector eventually with NAs.

`seqlevelsStyle(x)`, `seqlevelsStyle(x) <- value`: Get or set the seqname style for `x`. See the `seqlevelsStyle` generic getter and setter in the `GenomeInfoDb` package for more information.

`score(x)`, `score(x) <- value`: Get or set the "score" metadata column.

Tuples methods

In the following code snippets, `x` is a `GTuplesList` object.

WARNING: The preferred setter is `tuples(x) <- value` and the use of `start(x) <- value`, `end(x) <- value` and `width(x) <- value` is discouraged.

`start(x)`, `start(x) <- value`: Get or set pos_1 of the tuples. **WARNING:** The use of `start(x) <- value` is discouraged; instead, construct the tuples as the appropriate List of integer matrices, `mvalue`, and use `tuples(x) <- mvalue`.

`end(x)`, `end(x) <- value`: Get or set pos_m of the tuples, where m is the size of the tuples. **WARNING:** The use of `end(x) <- value` is discouraged; instead, construct the tuples as the appropriate List of integer matrices, `mvalue`, and use `tuples(x) <- mvalue`.

`IPD(x)`: Get the intra-pair distances (IPD) in the form of a `SimpleList` of integer matrices. IPD is only defined for tuples with size > 1 . The IPD of a tuple with size $= m$ is the vector of intra-pair distances, $(pos_2 - pos_1, \dots, pos_m - pos_{m-1})$.

`width(x)`, `width(x) <- value`: Get or set $pos_m - pos_1$ of the tuples, where m is the size of the tuples. If using `width(x) <- value`, pos_1 is held fixed and pos_m is altered. **WARNING:** The use of `width(x) <- value` is discouraged; instead, instead, construct the tuples as the appropriate List of integer matrices, `mvalue`, and use `tuples(x) <- mvalue`.

Coercion

In the code snippets below, `x` is a `GTuplesList` object.

`as.data.frame(x, row.names = NULL, optional = FALSE, ..., value.name = "value", use.outer = FALSE)`: Coerces `x` to a `data.frame`. See `as.data.frame` on the `List` man page for details (`?List`).

`as.list(x, use.names = TRUE)`: Creates a list containing the elements of `x`.

`as(x, "GRangesList")`: Creates a `GRangesList` object from a `GTuplesList` object. **WARNING:** This is generally a *destructive* operation, as the original `GTuplesList` may not be re-creatable.

Subsetting

In the following code snippets, `x` is a `GTuplesList` object.

`x[i, j]`, `x[i, j] <- value`: Get or set elements `i` with optional metadata columns `mcols(x)[, j]`, where `i` can be missing; an NA-free logical, numeric, or character vector; a 'logical' Rle object, or an `AtomicList` object.

`x[[i]]`, `x[[i]] <- value`: Get or set element `i`, where `i` is a numeric or character vector of length 1.

`x$name`, `x$name <- value`: Get or set element name, where name is a name or character vector of length 1.

`head(x, n = 6L)`: If `n` is non-negative, returns the first `n` elements of the `GTuplesList` object. If `n` is negative, returns all but the last `abs(n)` elements of the `GTuplesList` object.

`rep(x, times, length.out, each)`: Repeats the values in `x` through one of the following conventions:

`times` Vector giving the number of times to repeat each element if of length `length(x)`, or to repeat the whole vector if of length 1.

`length.out` Non-negative integer. The desired length of the output vector.

`each` Non-negative integer. Each element of `x` is repeated each times.

`subset(x, subset)`: Returns a new object of the same class as `x` made of the subset using logical vector `subset`, where missing values are taken as `FALSE`.

`tail(x, n = 6L)`: If `n` is non-negative, returns the last `n` elements of the `GTuples` object. If `n` is negative, returns all but the first `abs(n)` elements of the `GTuples` object.

Combining

In the code snippets below, `x` is a `GTuplesList` object.

`c(x, ...)`: Combines `x` and the `GTuplesList` objects in `...` together. Any object in `...` must belong to the same class as `x`, or to one of its subclasses, or must be `NULL`. The result is an object of the same class as `x`.

`append(x, values, after = length(x))`: Inserts the values into `x` at the position given by `after`, where `x` and `values` are of the same class.

`unlist(x, recursive = TRUE, use.names = TRUE)`: Concatenates the elements of `x` into a single `GTuples` object.

Looping

In the code snippets below, `x` is a `GTuplesList` object.

`endoapply(X, FUN, ...)`: Similar to `lapply`, but performs an endomorphism, i.e. returns an object of `class(X)`.

`lapply(X, FUN, ...)`: Like the standard `lapply` function defined in the base package, the `lapply` method for `GTuplesList` objects returns a list of the same length as `X`, with each element being the result of applying `FUN` to the corresponding element of `X`.

`Map(f, ...)`: Applies a function to the corresponding elements of given `GTuplesList` objects.

`mapply(FUN, ..., MoreArgs = NULL, SIMPLIFY = TRUE, USE.NAMES = TRUE)`: Like the standard `mapply` function defined in the base package, the `mapply` method for `GTuplesList` objects is a multivariate version of `sapply`.

`mendoapply(FUN, ..., MoreArgs = NULL)`: Similar to `mapply`, but performs an endomorphism across multiple objects, i.e. returns an object of `class(list(...)[[1]])`.

`Reduce(f, x, init, right = FALSE, accumulate = FALSE)`: Uses a binary function to successively combine the elements of `x` and a possibly given initial value.

f A binary argument function.

init An R object of the same kind as the elements of `x`.

right A logical indicating whether to proceed from left to right (default) or from right to left.

nomatch The value to be returned in the case when "no match" (no element satisfying the predicate) is found.

`sapply(X, FUN, ..., simplify=TRUE, USE.NAMES=TRUE)`: Like the standard `sapply` function defined in the base package, the `sapply` method for `GTuplesList` objects is a user-friendly version of `lapply` by default returning a vector or matrix if appropriate.

Author(s)

Peter Hickey for `GTuplesList` definition and methods. P. Aboyoun & H. Pages for all the real work underlying the powerful `GRangesList` class and methods.

See Also

[GTuples-class seqinfo](#), [GRangesList-class](#), [Vector-class](#), [RangesList-class](#), [RleList-class](#), [DataFrameList-class](#), [findOverlaps-methods](#)

Examples

```
## Construction of GTuplesList of 4-tuples with GTuplesList():
seqinfo <- Seqinfo(paste0("chr", 1:3), c(1000, 2000, 1500), NA, "mock1")
gt4 <- GTuples(seqnames = Rle(c("chr1", "chr2", "chr1", "chr3"),
                             c(1, 3, 2, 4)),
              tuples = matrix(c(1:10, 2:11, 3:12, 4:13), ncol = 4),
              strand = Rle(strand(c("-", "+", "*", "+", "-")),
                           c(1, 2, 2, 3, 2)),
              score = 1:10, GC = seq(1, 0, length = 10), seqinfo = seqinfo)
gtl4 <- GTuplesList(A = gt4[1:4], B = gt4[5:10])
gtl4

## Summarizing elements:
elementLengths(gtl4)
table(seqnames(gtl4))

## Extracting subsets:
gtl4[seqnames(gtl4) == "chr1", ]
gtl4[seqnames(gtl4) == "chr1" & strand(gtl4) == "+", ]

## Renaming the underlying sequences:
seqlevels(gtl4)
seqlevels(gtl4) <- sub("chr", "Chrom", seqlevels(gtl4))
gtl4

## Coerce to GRangesList ("internal positions" information is lost):
as(gtl4, "GRangesList")

## Get the size of the tuples stored in the GTuplesList object
size(gtl4)

## Get the tuples
tuples(gtl4)

## Get the matrix of intra-pair distances (IPD)
IPD(gtl4)

## Can't combine genomic tuples of different sizes
gt1 <- GTuples('chr1', matrix(30:40))
gt1
## Not run:
## Returns error
GTuplesList(A = gt4, gt1)

## End(Not run)
```

Description

This man page documents intra-tuple transformations of a [GTuples](#) or a [GTuplesList](#) object.

WARNING: These are not exactly the same as the intra-range methods defined in the **GenomicRanges** package (`?GenomicRanges::intra-range-methods`) or in the **IRanges** package (`?IRanges::intra-range-m`

Usage

```
## S4 method for signature 'GTuples'
shift(x, shift = 0L, use.names = TRUE)
## S4 method for signature 'GTuplesList'
shift(x, shift = 0L, use.names = TRUE)

## S4 method for signature 'GTuples'
trim(x, use.names = TRUE)
```

Arguments

`x` A [GTuples](#) or [GTuplesList](#) object.
`shift, use.names` See `?`intra-range-methods``.
`...` Additional arguments to methods.

Details

- `shift` behaves like the `shift` method for [GRanges](#) objects, except that any `internalPos` are also shifted. See `?`intra-range-methods`` for further details of the `shift` method.
- `trim` trims out-of-bound tuples located on non-circular sequences whose length is not NA.

Value

See Details section above.

Author(s)

Peter Hickey for methods involving [GTuples](#) and [GTuplesList](#). P. Aboyoun and V. Obenchain <vobencha@fhcrc.org> for all the real work underlying the powerful intra-range methods.

See Also

- [GTuples](#) and [GTuplesList](#) objects.
- The [intra-range-methods](#) man page in the **GenomicRanges** package.

Examples

```
## -----
## A. ON A GTuples OBJECT
## -----
gt3 <- GTuples(seqnames = c('chr1', 'chr1', 'chr1', 'chr1', 'chr2'),
              tuples = matrix(c(10L, 10L, 10L, 10L, 10L, 20L, 20L, 20L, 25L,
                               20L, 30L, 30L, 35L, 30L, 30L), ncol = 3),
              strand = c('+', '-', '*', '+', '+'))
gt3
```

```

shift(gt3, 10)

## -----
## B. ON A GTuplesList OBJECT
## -----
gtl3 <- GRangesList(A = gt3, B = rev(gt3))
gtl3

shift(gtl3, IntegerList(10, 100))

```

nearest-methods

Finding the nearest genomic tuple/range neighbor

Description

The nearest, precede, follow, distance and distanceToNearest methods for [GTuples](#) objects and subclasses.

NOTE: These methods treat the tuples as if they were ranges, with ranges given by $[pos_1, pos_m]$ and where m is the [size, GTuples-method](#) of the tuples. This is done via inheritance so that a [GTuples](#) object is treated as a [GRanges](#) and the appropriate method is dispatched upon.

Usage

```

## S4 method for signature 'GTuples,GTuples'
precede(x, subject, select = c("arbitrary", "all"),
        ignore.strand = FALSE, ...)
## S4 method for signature 'GTuples,missing'
precede(x, subject, select = c("arbitrary", "all"),
        ignore.strand = FALSE, ...)

## S4 method for signature 'GTuples,GTuples'
follow(x, subject, select = c("arbitrary", "all"),
        ignore.strand=FALSE, ...)
## S4 method for signature 'GTuples,missing'
follow(x, subject, select = c("arbitrary", "all"),
        ignore.strand = FALSE, ...)

## S4 method for signature 'GTuples,GTuples'
nearest(x, subject, select = c("arbitrary", "all"),
        ignore.strand = FALSE, ...)
## S4 method for signature 'GTuples,missing'
nearest(x, subject, select = c("arbitrary", "all"),
        ignore.strand = FALSE, ...)

## S4 method for signature 'GTuples,GTuples'
distanceToNearest(x, subject, ignore.strand = FALSE,
                  ...)
## S4 method for signature 'GTuples,missing'
distanceToNearest(x, subject, ignore.strand = FALSE,
                  ...)

```

```
## S4 method for signature 'GTuples,GTuples'
distance(x, y, ignore.strand = FALSE, ...)
```

Arguments

x	The query GTuples instance.
subject	The subject GTuples instance within which the nearest neighbors are found. Can be missing, in which case x is also the subject.
y	For the distance method, a GTuples or GRanges instance. Cannot be missing. If x and y are not the same length, the shortest will be recycled to match the length of the longest.
select	Logic for handling ties. By default, all methods select a single tuple/range (arbitrary for nearest, the first by order in subject for precede, and the last for follow). When select = "all" a Hits object is returned with all matches for x. If x does not have a match in subject the x is not included in the Hits object.
ignore.strand	A logical indicating if the strand of the input tuples/ranges should be ignored. When TRUE, strand is set to '+'.
...	Additional arguments for methods.

Details

- nearest: Performs conventional nearest neighbor finding. Returns an integer vector containing the index of the nearest neighbor tuple/range in subject for each range in x. If there is no nearest neighbor NA is returned. For details of the algorithm see the man page in [IRanges](#), ?nearest.
- precede: For each range in x, precede returns the index of the tuple/range in subject that is directly preceded by the tuple/range in x. Overlapping tuples/ranges are excluded. NA is returned when there are no qualifying tuples/ranges in subject.
- follow: The opposite of precede, follow returns the index of the tuple/range in subject that is directly followed by the tuple/range in x. Overlapping tuples/ranges are excluded. NA is returned when there are no qualifying tuples/ranges in subject.
- Orientation and Strand: The relevant orientation for precede and follow is 5' to 3', consistent with the direction of translation. Because positional numbering along a chromosome is from left to right and transcription takes place from 5' to 3', precede and follow can appear to have 'opposite' behavior on the + and - strand. Using positions 5 and 6 as an example, 5 precedes 6 on the + strand but follows 6 on the - strand.
A tuple/range with strand * can be compared to tuples/ranges on either the + or - strand. Below we outline the priority when tuples/ranges on multiple strands are compared. When ignore.strand=TRUE all tuples/ranges are treated as if on the + strand.
 - x on + strand can match to tuples/ranges on both + and * strands. In the case of a tie the first tuple/range by order is chosen.
 - x on - strand can match to tuples/ranges on both - and * strands. In the case of a tie the first tuple/range by order is chosen.
 - x on * strand can match to tuples/ranges on any of +, - or * strands. In the case of a tie the first tuple/range by order is chosen.
- distanceToNearest: Returns the distance for each tuple/range in x to its nearest neighbor in the subject.

- `distance`: Returns the distance for each tuple/range in `x` to the range in `y`. The behavior of `distance` has changed in Bioconductor 2.12. See the man page `?distance` in `IRanges` for details.

Value

For `nearest`, `precede` and `follow`, an integer vector of indices in `subject`, or a [Hits](#) if `select = "all"`.

For `distanceToNearest`, a [Hits](#) object with a column for the query index (`queryHits`), `subject` index (`subjectHits`) and the distance between the pair.

For `distance`, an integer vector of distances between the tuples/ranges in `x` and `y`.

Author(s)

Peter Hickey for methods involving [GTuples](#). P. Aboyoun and V. Obenchain <vobencha@fhcrc.org> for all the real work underlying the powerful nearest methods.

See Also

- The [GTuples](#) and [GRanges](#) classes.
- The [GenomicRanges](#) and [GRanges](#) classes in the **GenomicRanges** package.
- The [Ranges](#) class in the **IRanges** package.
- The [Hits](#) class in the **S4Vectors** package.
- The [nearest-methods](#) man page in the **GenomicRanges** package.
- [findOverlaps-methods](#) for finding just the overlapping ranges.

Examples

```
## -----
## precede() and follow()
## -----
query <- GTuples("A", matrix(c(5L, 20L, 6L, 21L), ncol = 2), strand = "+")
subject <- GTuples("A", matrix(c(rep(c(10L, 15L), 2), rep(c(11L, 16L), 2)),
                             ncol = 2),
                       strand = c("+", "+", "-", "-"))
precede(query, subject)
follow(query, subject)

strand(query) <- "-"
precede(query, subject)
follow(query, subject)

## ties choose first in order
query <- GTuples("A", matrix(c(10L, 11L), ncol = 2), c("+", "-", "*"))
subject <- GTuples("A", matrix(c(rep(c(5L, 15L), each = 3),
                               rep(c(6L, 16L), each = 3)), ncol = 2),
                    rep(c("+", "-", "*"), 2))
precede(query, subject)
precede(query, rev(subject))

## ignore.strand = TRUE treats all ranges as '+'
precede(query[1], subject[4:6], select="all", ignore.strand = FALSE)
precede(query[1], subject[4:6], select="all", ignore.strand = TRUE)
```

```

## -----
## nearest()
## -----
## When multiple tuples overlap an "arbitrary" tuple is chosen
query <- GTuples("A", matrix(c(5L, 15L), ncol = 2))
subject <- GTuples("A", matrix(c(1L, 15L, 5L, 19L), ncol = 2))
nearest(query, subject)

## select = "all" returns all hits
nearest(query, subject, select = "all")

## Tuples in 'x' will self-select when 'subject' is present
query <- GTuples("A", matrix(c(1L, 10L, 6L, 15L), ncol = 2))
nearest(query, query)

## Tuples in 'x' will not self-select when 'subject' is missing
nearest(query)

## -----
## distance(), distanceToNearest()
## -----
## Adjacent, overlap, separated by 1
query <- GTuples("A", matrix(c(1L, 2L, 10L, 5L, 8L, 11L), ncol = 2))
subject <- GTuples("A", matrix(c(6L, 5L, 13L, 10L, 10L, 15L), ncol = 2))
distance(query, subject)

## recycling
distance(query[1], subject)

query <- GTuples(c("A", "B"), matrix(c(1L, 5L, 2L, 6L), ncol = 2))
distanceToNearest(query, subject)

```

Undefined methods

Undefined methods

Description

These are methods defined for [GRanges](#) and [GRangesList](#) objects that have no well-defined equivalent for [GTuples](#) or [GTuplesList](#). Therefore, I have explicitly written methods for these that return errors when called.

Examples

```

gt3 <- GTuples(seqnames = c('chr1', 'chr1', 'chr1', 'chr1', 'chr2'),
              tuples = matrix(c(10L, 10L, 10L, 10L, 10L, 20L, 20L, 20L, 25L,
                              20L, 30L, 30L, 35L, 30L, 30L), ncol = 3),
              strand = c('+', '-', '*', '+', '+'))

## Not run:
# Will return errors
narrow(gt3)
reduce(gt3)

## End(Not run)

```

Index

*Topic **methods**

findOverlaps-methods, 2
GTuples-comparison, 11
intra-tuple-methods, 18

*Topic **utilities**

findOverlaps-methods, 2
intra-tuple-methods, 18
nearest-methods, 20

[, GTuples-method (GTuples-class), 5

[, GTuplesList, ANY-method
(GTuplesList-class), 14

[<-, GTuples, ANY, ANY, ANY-method
(GTuples-class), 5

[<-, GTuplesList, ANY, ANY, ANY-method
(GTuplesList-class), 14

[[<-, GTuplesList, ANY, ANY, ANY-method
(GTuplesList-class), 14

\$, GTuples-method (GTuples-class), 5

\$<-, GTuples, numeric-method
(GTuples-class), 5

%in%, 13

as.data.frame, GTuples-method
(GTuples-class), 5

c, GTuples-method (GTuples-class), 5

CharacterList, 15

class:GTuples (GTuples-class), 5

class:GTuplesList (GTuplesList-class),
14

coerce, GRanges, GTuples-method
(GTuples-class), 5

coerce, GTuplesList, data.frame-method
(GTuplesList-class), 14

coerce, GTuplesList, GRangesList-method
(GTuplesList-class), 14

coerce, GTuplesList, list-method
(GTuplesList-class), 14

compare, GTuples, GTuples-method
(GTuples-comparison), 11

CompressedIRangesList, 15

countOverlaps (findOverlaps-methods), 2

countOverlaps, GenomicRanges, GTuples-method
(findOverlaps-methods), 2

countOverlaps, GenomicRanges, GTuplesList-method
(findOverlaps-methods), 2

countOverlaps, GenomicRangesList, GTuples-method
(findOverlaps-methods), 2

countOverlaps, GenomicRangesList, GTuplesList-method
(findOverlaps-methods), 2

countOverlaps, GTuples, GenomicRanges-method
(findOverlaps-methods), 2

countOverlaps, GTuples, GenomicRangesList-method
(findOverlaps-methods), 2

countOverlaps, GTuples, GTuples-method
(findOverlaps-methods), 2

countOverlaps, GTuples, GTuplesList-method
(findOverlaps-methods), 2

countOverlaps, GTuples, Vector-method
(findOverlaps-methods), 2

countOverlaps, GTuplesList, GenomicRanges-method
(findOverlaps-methods), 2

countOverlaps, GTuplesList, GenomicRangesList-method
(findOverlaps-methods), 2

countOverlaps, GTuplesList, GTuples-method
(findOverlaps-methods), 2

countOverlaps, GTuplesList, GTuplesList-method
(findOverlaps-methods), 2

countOverlaps, GTuplesList, Vector-method
(findOverlaps-methods), 2

countOverlaps, Vector, GTuples-method
(findOverlaps-methods), 2

countOverlaps, Vector, GTuplesList-method
(findOverlaps-methods), 2

coverage, GTuples-method (Undefined
methods), 23

coverage, GTuplesList-method (Undefined
methods), 23

data.frame, 7

DataFrame, 6–9, 15

DataFrameList-class, 18

DataTable, 7

disjoin, GTuples-method (Undefined
methods), 23

disjoin, GTuplesList-method (Undefined
methods), 23

- disjointBins, GTuples-method (Undefined methods), 23
- distance, GTuples, GTuples-method (nearest-methods), 20
- distanceToNearest, GTuples, GTuples-method (nearest-methods), 20
- distanceToNearest, GTuples, missing-method (nearest-methods), 20
- DNAStrngSet, 9
- duplicated, 12, 13
- duplicated, GTuples-method (GTuples-comparison), 11
- duplicated.GTuples (GTuples-comparison), 11

- elementMetadata, GTuplesList-method (GTuplesList-class), 14
- elementMetadata<-, GTuples-method (GTuples-class), 5
- elementMetadata<-, GTuplesList-method (GTuplesList-class), 14
- end, GTuples-method (GTuples-class), 5
- end, GTuplesList-method (GTuplesList-class), 14
- end<-, GTuples-method (GTuples-class), 5
- end<-, GTuplesList-method (GTuplesList-class), 14

- findOverlaps, 2–4
- findOverlaps (findOverlaps-methods), 2
- findOverlaps, GenomicRanges, GTuples-method (findOverlaps-methods), 2
- findOverlaps, GenomicRanges, GTuplesList-method (findOverlaps-methods), 2
- findOverlaps, GRangesList, GTuples-method (findOverlaps-methods), 2
- findOverlaps, GRangesList, GTuplesList-method (findOverlaps-methods), 2
- findOverlaps, GTuples, GenomicRanges-method (findOverlaps-methods), 2
- findOverlaps, GTuples, GIntervalTree-method (findOverlaps-methods), 2
- findOverlaps, GTuples, GRangesList-method (findOverlaps-methods), 2
- findOverlaps, GTuples, GTuples-method (findOverlaps-methods), 2
- findOverlaps, GTuples, GTuplesList-method (findOverlaps-methods), 2
- findOverlaps, GTuples, RangedData-method (findOverlaps-methods), 2
- findOverlaps, GTuples, RangesList-method (findOverlaps-methods), 2
- findOverlaps, GTuplesList, GenomicRanges-method (findOverlaps-methods), 2
- findOverlaps, GTuplesList, GRangesList-method (findOverlaps-methods), 2
- findOverlaps, GTuplesList, GTuples-method (findOverlaps-methods), 2
- findOverlaps, GTuplesList, GTuplesList-method (findOverlaps-methods), 2
- findOverlaps, GTuplesList, RangedData-method (findOverlaps-methods), 2
- findOverlaps, GTuplesList, RangesList-method (findOverlaps-methods), 2
- findOverlaps, RangedData, GTuples-method (findOverlaps-methods), 2
- findOverlaps, RangedData, GTuplesList-method (findOverlaps-methods), 2
- findOverlaps, RangesList, GTuples-method (findOverlaps-methods), 2
- findOverlaps, RangesList, GTuplesList-method (findOverlaps-methods), 2
- findOverlaps-methods, 2, 13, 18, 22
- flank, GTuples-method (Undefined methods), 23
- flank, GTuplesList-method (Undefined methods), 23
- follow, GTuples, GTuples-method (nearest-methods), 20
- follow, GTuples, missing-method (nearest-methods), 20

- GAlignmentPairs, 2, 9
- GAlignments, 2, 9
- GAlignmentsList, 2
- gaps, GTuples-method (Undefined methods), 23
- GenomicRanges, 2, 9, 22
- GenomicRanges-comparison, 13
- GenomicTuples-package, 2
- GIntervalTree, 2, 4
- GRanges, 3–6, 9, 19, 20, 22, 23
- granges, GTuples-method (GTuples-class), 5
- GRangesList, 2–4, 14, 16, 23
- GRangesList-class, 18
- GTuples, 2–4, 11–14, 19–23
- GTuples (GTuples-class), 5
- GTuples-class, 5, 18
- GTuples-comparison, 11
- GTuplesList, 2–4, 15, 19, 23
- GTuplesList (GTuplesList-class), 14
- GTuplesList-class, 14

- Hits, 4, 12, 13, 21, 22

- intersect, GTuples, GTuples-method (Undefined methods), 23
- intra-range-methods, 19
- intra-tuple-methods, 13, 18
- IPD (GTuples-class), 5
- IPD, GTuples-method (GTuples-class), 5
- IPD, GTuplesList-method (GTuplesList-class), 14
- IRanges, 5, 9
- isDisjoint, GTuples-method (Undefined methods), 23
- isDisjoint, GTuplesList-method (Undefined methods), 23
- lapply, 17
- length, GTuples-method (GTuples-class), 5
- mapCoords, GTuples, GTuples-method (Undefined methods), 23
- mapCoords, GTuples, GTuplesList-method (Undefined methods), 23
- mapply, 17
- match, GTuples, GTuples-method (GTuples-comparison), 11
- names, GTuples-method (GTuples-class), 5
- names<-, GTuples-method (GTuples-class), 5
- narrow (Undefined methods), 23
- narrow, GTuples-method (Undefined methods), 23
- nearest, GTuples, GTuples-method (nearest-methods), 20
- nearest, GTuples, missing-method (nearest-methods), 20
- nearest-methods, 20, 22
- Ops, GTuples, numeric-method (Undefined methods), 23
- order, 13
- order, GTuples-method (GTuples-comparison), 11
- overlapsAny (findOverlaps-methods), 2
- overlapsAny, GRanges, GTuples-method (findOverlaps-methods), 2
- overlapsAny, GRanges, GTuplesList-method (findOverlaps-methods), 2
- overlapsAny, GRangesList, GTuples-method (findOverlaps-methods), 2
- overlapsAny, GRangesList, GTuplesList-method (findOverlaps-methods), 2
- overlapsAny, GTuples, GRanges-method (findOverlaps-methods), 2
- overlapsAny, GTuples, GTuplesList-method (findOverlaps-methods), 23
- overlapsAny, GTuples, GTuplesList-method (findOverlaps-methods), 2
- overlapsAny, GTuples, RangedData-method (findOverlaps-methods), 2
- overlapsAny, GTuples, RangesList-method (findOverlaps-methods), 2
- overlapsAny, GTuplesList, GRanges-method (findOverlaps-methods), 2
- overlapsAny, GTuplesList, GRangesList-method (findOverlaps-methods), 2
- overlapsAny, GTuplesList, GTuples-method (findOverlaps-methods), 2
- overlapsAny, GTuplesList, GtuplesList-method (findOverlaps-methods), 2
- overlapsAny, GTuplesList, RangedData-method (findOverlaps-methods), 2
- overlapsAny, GTuplesList, RangesList-method (findOverlaps-methods), 2
- overlapsAny, RangedData, GTuples-method (findOverlaps-methods), 2
- overlapsAny, RangedData, GTuplesList-method (findOverlaps-methods), 2
- overlapsAny, RangesList, GTuples-method (findOverlaps-methods), 2
- overlapsAny, RangesList, GTuplesList-method (findOverlaps-methods), 2
- pgap, GTuples, GTuples-method (Undefined methods), 23
- pintersect, GTuples, GTuples-method (Undefined methods), 23
- pintersect, GTuples, GTuplesList-method (Undefined methods), 23
- pintersect, GTuplesList, GTuples-method (Undefined methods), 23
- pintersect, GTuplesList, GTuplesList-method (Undefined methods), 23
- pmapCoords, GTuples, GTuplesList-method (Undefined methods), 23
- precede, GTuples, GTuples-method (nearest-methods), 20
- precede, GTuples, missing-method (nearest-methods), 20
- promoters, GTuples-method (Undefined methods), 23
- promoters, GTuplesList-method (Undefined methods), 23
- psetdiff, GTuples, GTuples-method (Undefined methods), 23
- overlapsAny, GTuples, GRangesList-method (findOverlaps-methods), 2

- psetdiff, GTuples, GTuplesList-method (Undefined methods), 23
- psetdiff, GTuplesList, GTuplesList-method (Undefined methods), 23
- punion, GTuples, GTuples-method (Undefined methods), 23
- punion, GTuples, GTuplesList-method (Undefined methods), 23
- punion, GTuplesList, GTuples-method (Undefined methods), 23
- range, GTuples-method (Undefined methods), 23
- range, GTuplesList-method (Undefined methods), 23
- RangedData, 3
- Ranges, 2, 22
- ranges, GTuples-method (GTuples-class), 5
- ranges, GTuplesList-method (GTuplesList-class), 14
- ranges<-, GTuples-method (GTuples-class), 5
- ranges<-, GTuplesList-method (GTuplesList-class), 14
- RangesList, 2, 3, 15
- RangesList-class, 18
- rank, 13
- rank, GTuples-method (GTuples-comparison), 11
- reduce, GTuples-method (Undefined methods), 23
- reduce, GTuplesList-method (Undefined methods), 23
- relistToClass, GTuples-method (GTuplesList-class), 14
- replaceROWS, NULL-method (Undefined methods), 23
- resize, GTuples-method (Undefined methods), 23
- resize, GTuplesList-method (Undefined methods), 23
- restrict, GTuplesList-method (Undefined methods), 23
- Rle, 5–8
- RleList, 15
- RleList-class, 18
- sapply, 17
- score, GTuples-method (GTuples-class), 5
- score, GTuplesList-method (GTuplesList-class), 14
- score<-, GTuples-method (GTuples-class), 5
- score<-, GTuplesList-method (GTuplesList-class), 14
- Seqinfo, 15
- seqinfo, 9, 18
- seqinfo, GTuples-method (GTuples-class), 5
- seqinfo, GTuplesList-method (GTuplesList-class), 14
- seqinfo<-, GTuples-method (GTuples-class), 5
- seqinfo<-, GTuplesList-method (GTuplesList-class), 14
- seqlevels, 7, 15
- seqlevelsStyle, 7, 15
- seqnames, 3
- seqnames, GTuples-method (GTuples-class), 5
- seqnames, GTuplesList-method (GTuplesList-class), 14
- seqnames<-, GTuples-method (GTuples-class), 5
- seqnames<-, GTuplesList-method (GTuplesList-class), 14
- setdiff, GTuples, GTuples-method (Undefined methods), 23
- shift (intra-tuple-methods), 18
- shift, GTuples-method (intra-tuple-methods), 18
- shift, GTuplesList-method (intra-tuple-methods), 18
- show, GTuples-method (GTuples-class), 5
- show, GTuplesList-method (GTuplesList-class), 14
- SimpleList, 15, 16
- size (GTuples-class), 5
- size, GTuples-method (GTuples-class), 5
- size, GTuplesList-method (GTuplesList-class), 14
- sort, 13
- sort, GTuples-method (GTuples-comparison), 11
- sort.GTuples (GTuples-comparison), 11
- splitAsListReturnedClass, GTuplesList-method (GTuplesList-class), 14
- start, GTuples-method (GTuples-class), 5
- start, GTuplesList-method (GTuplesList-class), 14
- start<-, GTuples-method (GTuples-class), 5
- start<-, GTuplesList-method (GTuplesList-class), 14
- strand, 3, 5

- strand, GTuples-method (GTuples-class), 5
- strand, GTuplesList-method (GTuplesList-class), 14
- strand<-, GTuples-method (GTuples-class), 5
- strand<-, GTuplesList, ANY-method (GTuplesList-class), 14
- strand<-, GTuplesList, character-method (GTuplesList-class), 14
- subsetByOverlaps (findOverlaps-methods), 2
- subsetByOverlaps, GRanges, GTuples-method (findOverlaps-methods), 2
- subsetByOverlaps, GRanges, GTuplesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GRangesList, GTuples-method (findOverlaps-methods), 2
- subsetByOverlaps, GRangesList, GTuplesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuples, GRanges-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuples, GRangesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuples, GTuples-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuples, GTuplesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuples, RangedData-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuples, RangesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuplesList, GRanges-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuplesList, GRangesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuplesList, GTuples-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuplesList, GTuplesList-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuplesList, RangedData-method (findOverlaps-methods), 2
- subsetByOverlaps, GTuplesList, RangesList-method (findOverlaps-methods), 2
- subsetByOverlaps, RangedData, GTuples-method (findOverlaps-methods), 2
- subsetByOverlaps, RangedData, GTuplesList-method (findOverlaps-methods), 2
- subsetByOverlaps, RangesList, GTuples-method (findOverlaps-methods), 2
- subsetByOverlaps, RangesList, GTuplesList-method (findOverlaps-methods), 2
- tile, GTuples-method (Undefined methods), 23
- trim, GTuples-method (intra-tuple-methods), 18
- tuples, 12
- tuples (GTuples-class), 5
- tuples, GTuples-method (GTuples-class), 5
- tuples, GTuplesList-method (GTuplesList-class), 14
- tuples<- (GTuples-class), 5
- tuples<-, GTuples-method (GTuples-class), 5
- tuples<-, GTuplesList-method (GTuplesList-class), 14
- Undefined methods, 23
- union, GTuples, GTuples-method (Undefined methods), 23
- unique, 12, 13
- updateObject, GTuplesList-method (GTuplesList-class), 14
- updateObject, GTuples-method (GTuples-class), 5
- Vector-class, 18
- width, GTuples-method (GTuples-class), 5
- width, GTuplesList-method (GTuplesList-class), 14
- width<-, GTuples-method (GTuples-class), 5
- width<-, GTuplesList-method (GTuplesList-class), 14
- window, GTuples-method (GTuples-class), 5