

Package ‘treekoR’

February 25, 2025

Type Package

Title Cytometry Cluster Hierarchy and Cellular-to-phenotype Associations

Version 1.14.0

biocViews Clustering, DifferentialExpression, FlowCytometry, ImmunoOncology, MassSpectrometry, SingleCell, Software, StatisticalMethod, Visualization

Description treekoR is a novel framework that aims to utilise the hierarchical nature of single cell cytometry data to find robust and interpretable associations between cell subsets and patient clinical end points. These associations are aimed to recapitulate the nested proportions prevalent in workflows involving manual gating, which are often overlooked in workflows using automatic clustering to identify cell populations. We developed treekoR to:
Derive a hierarchical tree structure of cell clusters; quantify a cell types as a proportion relative to all cells in a sample (%total), and, as the proportion relative to a parent population (%parent); perform significance testing using the calculated proportions; and provide an interactive html visualisation to help highlight key results.

Depends R (>= 4.1)

Imports stats, utils, tidyr, dplyr, data.table, ggiraph, ggplot2, hopach, ape, ggtree, patchwork, SingleCellExperiment, diffcyt, edgeR, lme4, multcomp

License GPL-3

Encoding UTF-8

LazyData false

RoxygenNote 7.2.3

Suggests knitr, rmarkdown, BiocStyle, CATALYST, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/treekoR>

git_branch RELEASE_3_20

git_last_commit ddac7bd

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-02-24

Author Adam Chan [aut, cre],
Ellis Patrick [ctb]

Maintainer Adam Chan <adam.s.chan@sydney.edu.au>

Contents

| | |
|----------------------------------|-----------|
| addFreqBars | 2 |
| addHeatMap | 3 |
| addTree | 4 |
| colourTree | 4 |
| DeBiasi_COVID_CD8_samp | 5 |
| findChildren | 6 |
| geometricMean | 6 |
| getCellGMeans | 7 |
| getCellProp | 8 |
| getClusterTree | 9 |
| getParentProp | 10 |
| getTotalProp | 10 |
| getTreeResults | 11 |
| hopachToPhylo | 12 |
| plotInteractiveHeatmap | 12 |
| plotSigScatter | 14 |
| runEdgeRTests | 15 |
| runGLMMTests | 15 |
| runHOPACH | 16 |
| testTree | 17 |
| Index | 19 |

| | |
|-------------|--------------|
| addFreqBars | <i>Title</i> |
|-------------|--------------|

Description

a function to add the frequency bars for each cluster

Usage

```
addFreqBars(
  p,
  clusters,
  offset = 0.75,
  bar_length = 3,
  bar_width = 0.4,
  freq_labels = FALSE
)
```

Arguments

| | |
|-------------|---|
| p | a phylogenetic tree plot created from the <code>ggtree()</code> function |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric) |
| offset | distance between the heatmap and frequency bars |
| bar_length | length of bar with max frequency |
| bar_width | width of each frequency bar |
| freq_labels | boolean indicated whether or not to show frequency bar labels |

Value

an interactive `ggplot` graph object with frequency bars of clusters alongside heatmap of cluster median expression

| | |
|------------|--------------|
| addHeatMap | <i>Title</i> |
|------------|--------------|

Description

a function to add a heatmap of cluster medians alongside the phylogenetic tree

Usage

```
addHeatMap(
  p,
  cluster_medians,
  offset = 0.5,
  width = 1,
  expand_y_lim = 20,
  low = "#313695",
  mid = "ivory",
  high = "#A50026",
  colnames_angle = 90,
  metric_name = "Column z-score"
)
```

Arguments

| | |
|-----------------|--|
| p | a phylogenetic tree plot created from the <code>ggtree()</code> function |
| cluster_medians | a dataframe with the cluster medians. The rownumbers of the clusters median data frame should correspond to the nodes in the phylo tree. The column names should also correspond to the labels you want to use |
| offset | the distance between the tree plot and heatmap |
| width | width of each tile in the heatmap |
| expand_y_lim | white space below heatmap |
| low | colour used for low values on heatmap |
| mid | colour used for medium values on heatmap |

high colour used for large values on heatmap
 colnames_angle angle for x-axis label
 metric_name legend title

Value

an interactive ggplot graph object with heatmap of median cluster expressions plotted alongside hierarchical tree

| | |
|---------|--------------|
| addTree | <i>Title</i> |
|---------|--------------|

Description

a function to create a skeleton tree diagram to display significance testing results on each node

Usage

```
addTree(p, offset = 0.3, font_size = 2.5, hjust = 0)
```

Arguments

p a phylogenetic tree plot created from the ggtree() function
 offset distance between leaf nodes on the tree and their labels
 font_size font size of leaf labels
 hjust horizontal justification as defined in ggplot2

Value

a ggtree graph object with the hierarchical tree of clusters and corresponding labels

| | |
|------------|-------------------|
| colourTree | <i>colourTree</i> |
|------------|-------------------|

Description

Adding statistical test results onto the tree by using colourful nodes and branches Takes a ggtree object with test results for each node and returns a ggtree graph object

Usage

```
colourTree(  
  tree,  
  point_size = 1.5,  
  high = "#00c434",  
  low = "purple",  
  mid = "ivory2"  
)
```

Arguments

| | |
|------------|--|
| tree | a tree plot created from the <code>ggtree()</code> function with <code>p\$data</code> containing test statistic and p- |
| point_size | size of nodes in the tree |
| high | colour for large values |
| low | colour for low values |
| mid | colour for middle values |

Value

an interactive ggplot graph object, plotting the hierarchical tree of clusters with nodes and branches coloured by the significance testing results.

Examples

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

tested_tree <- testTree(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes)

colourTree(tested_tree)
```

DeBiasi_COVID_CD8_samp

COVID-19 Sample data

Description

Data from a an experiment investigating T cell compositions between COVID-19 patients and healthy control. This data has been transformed using a `arcsinh` transform using a co-factor of 5 and randomly subsetted

Usage

```
data(COVIDSampleData)
```

Format

An object of class "SingleCellExperiment"

Source

[FlowRepository](#)

References

De Biasi et al. (2020) Nat Commun 11, 3434 ([Nature](#))

Examples

```
data(COVIDSampleData)
```

| | |
|--------------|---------------------|
| findChildren | <i>findChildren</i> |
|--------------|---------------------|

Description

findChildren

Usage

```
findChildren(tree)
```

Arguments

tree a ggtree object

Value

a ggtree object with the data containing a column with the clusters contained in each node

| | |
|---------------|----------------------|
| geometricMean | <i>geometricMean</i> |
|---------------|----------------------|

Description

getCellGMeans helper function

Usage

```
geometricMean(x, na.rm = TRUE)
```

Arguments

x vector containing numeric values
na.rm whether or not to ignore NA values

Value

geomtric mean of vector x

getCellGMeans *getCellGMeans*

Description

getCellGMeans

Usage

```
getCellGMeans(phylo, exprs, clusters, samples, classes)
```

Arguments

| | |
|----------|--|
| phylo | a phylogram with tip.labels corresponding to cell types/cluster contained in 'clusters' vector |
| exprs | a dataframe containing single cell expression data |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1. |
| samples | a vector identifying the patient each cell belongs to |
| classes | a vector containing the patient outcome/class each cell belongs to |

Value

a dataframe containing proportions calculated for each sample

Examples

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

means_df <- getCellGMeans(clust_tree$clust_tree,
                          exprs=exprs,
                          clusters=clusters,
                          samples=samples,
                          classes=classes)
```

| | |
|-------------|--------------------|
| getCellProp | <i>getCellProp</i> |
|-------------|--------------------|

Description

getCellProp

Usage

```
getCellProp(phylo, clusters, samples, classes, excl_top_node_parent = TRUE)
```

Arguments

| | |
|----------------------|--|
| phylo | a phylogram with tip.labels corresponding to cell types/cluster contained in 'clusters' vector |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1. |
| samples | a vector identifying the patient each cell belongs to |
| classes | a vector containing the patient outcome/class each cell belongs to |
| excl_top_node_parent | a boolean indicating whether the for cell types with the highest node as their parent |

Value

a dataframe containing proportions calculated for each sample

Examples

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

prop_df <- getCellProp(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes)
```

| | |
|---------------|----------------------|
| getParentProp | <i>getParentProp</i> |
|---------------|----------------------|

Description

getCellProp helper function

Usage

```
getParentProp(vars1, vars2, n_cells)
```

Arguments

| | |
|---------|---|
| vars1 | name of cell type, matching to column in n_cells |
| vars2 | name of parent cell type, matching to column in n_cells |
| n_cells | matrix of counts of each cell type per sample |

Value

a vector containing the proportions of cell type vars1 as a percent of parent vars2 per sample

| | |
|--------------|---------------------|
| getTotalProp | <i>getTotalProp</i> |
|--------------|---------------------|

Description

getCellProp helper function

Usage

```
getTotalProp(vars1, n_cells, n_cells_pat)
```

Arguments

| | |
|-------------|--|
| vars1 | name of cell type, matching to column in n_cells |
| n_cells | matrix of counts of each cell type per sample |
| n_cells_pat | vector containing number of cells per sample |

Value

a vector containing the proportions of cell type vars1 as a percent of total per sample

| | |
|----------------|-----------------------|
| getTreeResults | <i>getTreeResults</i> |
|----------------|-----------------------|

Description

getTreeResults

Usage

```
getTreeResults(testedTree, sort_by = "parent")
```

Arguments

| | |
|------------|--|
| testedTree | a ggtree object outputed from testTree() |
| sort_by | whether to sort by p-values testing via proportions to parent or p-values testing via absolute proportions. Values can be c(NA, "parent", "all") |

Value

a dataframe with hierarchical tree nodes, corresponding clusters and corresponding significance testing results

Examples

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

tested_tree <- testTree(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes,
                       pos_class_name=NULL)

res_df <- getTreeResults(tested_tree)

head(res_df, 10)
```

| | |
|---------------|----------------------|
| hopachToPhylo | <i>hopachToPhylo</i> |
|---------------|----------------------|

Description

hopachToPhylo

Usage

```
hopachToPhylo(res)
```

Arguments

res an object returned from the runHOPACH() function

Value

a phylogram converted from the outputted list from the runHOPACH function

Examples

```
library(SingleCellExperiment)
library(data.table)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_med_dt <- as.data.table(exprs)
clust_med_dt[, cluster_id := clusters]
res <- clust_med_dt[, lapply(.SD, median, na.rm=TRUE), by=cluster_id]
res2 <- res[, .SD, .SDcols = !c('cluster_id')]

hopach_res <- runHOPACH(as.data.frame(scale(res2)))
phylo <- hopachToPhylo(hopach_res)
```

plotInteractiveHeatmap

Title

Description

This function takes a hierarchical tree which has been tested for proportion to all and proportion to parent cluster

Usage

```

plotInteractiveHeatmap(
  testedTree,
  clust_med_df,
  clusters,
  svg_width = 13,
  svg_height = 9,
  tr_offset = 0.3,
  tr_font_size = 2,
  tr_point_size = 1.5,
  tr_col_high = "#00c434",
  tr_col_low = "purple",
  tr_col_mid = "ivory2",
  hm_offset = 1,
  hm_tile_width = 1,
  hm_expand_y_lim = 20,
  hm_col_high = "#cc2010",
  hm_col_mid = "#fff8de",
  hm_col_low = "#66a6cc",
  fb_offset = 0.75,
  fb_bar_length = 3,
  fb_bar_width = 0.4,
  fb_freq_labels = FALSE
)

```

Arguments

| | |
|-----------------|--|
| testedTree | a ggtree object that has been run through the testTree |
| clust_med_df | a dataframe with the cluster medians. The rownumbers of the clusters median data frame should correspond to the nodes in the phylo tree. The column names should also correspond to the labels you want to use |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric) |
| svg_width | width of svg canvas |
| svg_height | height of svf canvas |
| tr_offset | distance between leaf nodes on the tree and their labels |
| tr_font_size | font size of leaf labels |
| tr_point_size | size of each node in the tree |
| tr_col_high | colour used for high test statistics, coloured on the nodes and branches of the tree |
| tr_col_low | colour used for low test statistics, coloured on the nodes and branches of the tree |
| tr_col_mid | colour used for medium test statistics, coloured on the nodes and branches of the tree |
| hm_offset | distance between the tree and the heatmap |
| hm_tile_width | width of each tile in the heatmap |
| hm_expand_y_lim | white space below heatmap |
| hm_col_high | colour used for large values on heatmap |

hm_col_mid colour used for medium values on heatmap
 hm_col_low colour used for low values on heatmap
 fb_offset distance between the heatmap and frequency bars
 fb_bar_length length of bar with max frequency
 fb_bar_width width of each frequency bar
 fb_freq_labels boolean indicated whether or not to show frequency bar labels

Value

an interactive ggplot object containing the hierarchical tree of clusters coloured by significance testing results, with corresponding heatmap and a scatterplot comparing significance when testing using proportions to parent vs. absolute proportions

Examples

```

library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_tree <- getClusterTree(exprs,
                             clusters,
                             hierarchy_method="hopach")

tested_tree <- testTree(clust_tree$clust_tree,
                       clusters=clusters,
                       samples=samples,
                       classes=classes)

plotInteractiveHeatmap(tested_tree,
                      clust_med_df = clust_tree$median_freq,
                      clusters=clusters)

```

plotSigScatter

plotSigScatter

Description

plotSigScatter

Usage

```
plotSigScatter(testedTree, scatter_tooltip, max_val)
```

Arguments

testedTree an output from the function testTree()
 scatter_tooltip vector containing tooltips for interactive plot
 max_val maximum value to set as x/y axis limits

Value

a ggplot object, containing test statistics from testing proportions relative to parent against the test statistics from testing absolute proportions.

| | |
|---------------|----------------------|
| runEdgeRTests | <i>runEdgeRTests</i> |
|---------------|----------------------|

Description

This function runs edgeR using the treekoR inputs across all nodes of the hierarchical tree of clusters, adapted from the diffcyt workflow

Usage

```
runEdgeRTests(td, clusters, samples, classes, pos_class_name)
```

Arguments

| | |
|----------------|--|
| td | a dataframe of data from ggtree object |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1. |
| samples | a vector identifying the patient each cell belongs to |
| classes | a vector containing the patient outcome/class each cell belongs to |
| pos_class_name | a character indicating which class should be treated as positive |

Value

a dataframe with pvalues, test statistic (signed $-\log_{10}(p)$), and FDR

| | |
|--------------|---------------------|
| runGLMMTests | <i>runGLMMTests</i> |
|--------------|---------------------|

Description

This function runs GLMM using the treekoR inputs across all nodes of the hierarchical tree of clusters, adapted from the diffcyt workflow. (Unable to get direction of test statistic currently)

Usage

```
runGLMMTests(td, clusters, samples, classes, pos_class_name, neg_class_name)
```

Arguments

| | |
|----------------|--|
| td | a dataframe of data from ggtree object |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1. |
| samples | a vector identifying the patient each cell belongs to |
| classes | a vector containing the patient outcome/class each cell belongs to |
| pos_class_name | a character indicating which class should be treated as positive |
| neg_class_name | a character indicating which class should be treated as negative |

Value

a dataframe with pvalues and test statistics

| | |
|-----------|------------------|
| runHOPACH | <i>runHOPACH</i> |
|-----------|------------------|

Description

runHOPACH

Usage

```
runHOPACH(data, K = 10, kmax = 5, dissimilarity_metric = "cor")
```

Arguments

| | |
|----------------------|---|
| data | dataframe containing the median expression of the clusters/cell types |
| K | positive integer specifying the maximum number of levels in the tree. Must be 15 or less, due to computational limitations (overflow) |
| kmax | integer between 1 and 9 specifying the maximum number of children at each node in the tree |
| dissimilarity_metric | metric used to calculate dissimilarities between clusters/cell types |

Value

a list containing the groups each cluster belongs to at each level of the hopach tree

Examples

```
library(SingleCellExperiment)
library(data.table)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id

clust_med_dt <- as.data.table(exprs)
clust_med_dt[, cluster_id := clusters]
res <- clust_med_dt[, lapply(.SD, median, na.rm=TRUE), by=cluster_id]
res2 <- res[, .SD, .SDcols = !c('cluster_id')]

hopach_res <- runHOPACH(as.data.frame(scale(res2)))
```

| | |
|----------|-----------------|
| testTree | <i>testTree</i> |
|----------|-----------------|

Description

This function takes a hierarchical tree of the cluster medians of a cytometry dataset, and then uses this structure to perform t-tests between conditions of patients testing for difference using the proportion of cluster relative to sample's n and proportion of cluster relative to sample's n of hierarchical parent cluster. Takes a ggtree object and returns a ggtree object with testing results appended in the data

Usage

```
testTree(
  phylo,
  clusters,
  samples,
  classes,
  sig_test = "ttest",
  p_adjust = NULL,
  pos_class_name = NULL
)
```

Arguments

| | |
|----------------|--|
| phylo | a ggtree object |
| clusters | a vector representing the cell type or cluster of each cell (can be character or numeric). If numeric, cluster names need to be consecutive starting from 1. |
| samples | a vector identifying the patient each cell belongs to |
| classes | a vector containing the patient outcome/class each cell belongs to |
| sig_test | a character, either "ttest" or "wilcox" indicating the significance test to be used |
| p_adjust | a character, indicating whether p-value adjustment should be performed. Valid values are in stats::p.adjust.methods |
| pos_class_name | a character indicating which class is positive |

Value

a ggtree object with significance testing results in embedded data

Examples

```
library(SingleCellExperiment)
data(COVIDSampleData)

sce <- DeBiasi_COVID_CD8_samp
exprs <- t(assay(sce, "exprs"))
clusters <- colData(sce)$cluster_id
classes <- colData(sce)$condition
samples <- colData(sce)$sample_id
```

```
clust_tree <- getClusterTree(exprs,  
                             clusters,  
                             hierarchy_method="hopach")  
  
tested_tree <- testTree(clust_tree$clust_tree,  
                        clusters=clusters,  
                        samples=samples,  
                        classes=classes,  
                        sig_test="ttest",  
                        pos_class_name=NULL)
```

Index

* datasets

DeBiasi_COVID_CD8_samp, [5](#)

addFreqBars, [2](#)

addHeatMap, [3](#)

addTree, [4](#)

colourTree, [4](#)

DeBiasi_COVID_CD8_samp, [5](#)

findChildren, [6](#)

geometricMean, [6](#)

getCellMeans, [7](#)

getCellProp, [8](#)

getClusterTree, [9](#)

getParentProp, [10](#)

getTotalProp, [10](#)

getTreeResults, [11](#)

hopachToPhylo, [12](#)

plotInteractiveHeatmap, [12](#)

plotSigScatter, [14](#)

runEdgeRTests, [15](#)

runGLMMTests, [15](#)

runHOPACH, [16](#)

testTree, [17](#)